

TITLE OF THE INVENTION

NETWORK DEVICE AND METHOD

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2002-245373, filed August 26, 2002, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The invention relates to improvement of a network device and a network method, by which mutual transmission/reception of data is realized among networks with different standards from each other.

15 2. Description of the Related Art

Recently, it has been possible to construct a network system in which two or more pieces of AV (Audio Video) equipment are connected to each other in a free form by a serial bus using a digital interface
20 according to the IEEE (Institute of Electrical and Electronics Engineers) 1394 standard, as is generally known.

Moreover, the IEEE 1394. 1 standard has existed in order to connect a network according to the IEEE 1394
25 standard and another network constructed according to a standard other than IEEE 1394 and to transmit/receive data between both networks. In the IEEE 1394. 1

standard, an equipment (node) which functions as a conduit between networks is called as a bridge. The following processing is executed in the bridge:

(1) The node which functions as a bridge notifies
5 each network of its own bridge function, using an extended flag in a Self_ID packet. Thereby, each node (AV equipment) constructing each network understands the extended flag supplied from the bridge.

(2) Each network is processed as a different bus
10 from each other. That is, each network has individual Bus_IDs which are defined in the IEEE 1394 standard. Accordingly, each node in one network can access those in other networks, using the Bus_IDs.

(3) Destination addresses (Node_IDs in the IEEE
15 1394 standard) of each node (AV equipment) constructing other networks are managed by the bridge which assigns virtual Node_IDs.

However, the following problems have been caused in the above-described network bridge:

(1) In the application of the IEEE 1394. 1
20 standard, conformity of even a physical layer level to the standard is required and modifications are indispensable in LSIs (Large Scale Integration) meeting the current IEEE 1394a-2000 standard, for it is
25 indicated by the extended flag in the Self_ID packet which node manages the virtual IDs, that is, which one is the bridge. Therefore, the conformity to the

standard becomes difficult in the existing equipment which has already been marketed.

(2) Although each node in a network accesses nodes in other networks, using the Bus_IDs, there has also
5 existed a network which has a protocol under which the Bus_IDs cannot be used. For example, in the protocol standard of the IEC (International Electrotechnical Commission) 61883 in which data transmission according to MPEG (Moving Picture Experts Group) 2-TS (Transport
10 Stream) and the like is executed under use of isochronous packets, the Bus_IDs are not used and only Physical_IDs are utilized in order to indicate the source of the isochronous packets. Accordingly, a source cannot be identified in the case of a packet
15 from another network with a different Bus_ID. Here, a Node_ID which indicates a destination in the IEEE 1394 standard is expressed as follows:

Node_ID = Bus_ID (ten bits) + Physical_ID
(six bits)

20 BRIEF SUMMARY OF THE INVENTION

According to one aspect of the present invention, there is provided a network device comprising:

a first connection section configured to be connected to a first network;

25 a second connection section configured to be connected to a second network different from the first network;

a control section configured to detect equipment connected to the second network through the second connection section, to generate identification information by which the detected equipment is added to the first network, and to transmit the information to the first network through the first connection section.

According to one aspect of the present invention, there is provided a network method of making data transmission between a first network and a second network different from the first network, comprising:

requiring construction by which equipment connected to the second network is added to the first network; and

transmitting identification information, by which equipment connected to the second network is added to the first network, to the first network in a state where the construction is required.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 is a block diagram showing one embodiment according to the invention and explaining a state where two kinds of networks are connected to each other through a bridging device;

FIG. 2 is a block diagram explaining a detailed configuration of the bridging device in the embodiment;

FIG. 3 is a block diagram explaining a state where the two kinds of networks in the embodiment are virtually connected as one network;

FIG. 4 is a flow chart explaining operations by which a piece of equipment in one network recognizes another piece of equipment in the other network according to the embodiment; and

5 FIG. 5 is a flow chart explaining operations by which data transmission is executed from a piece of equipment in one network to another piece of equipment in the other network according to the embodiment.

DETAILED DESCRIPTION OF THE INVENTION

10 Hereinafter, one embodiment according to the invention will be explained in detail, referring to drawings. In FIG. 1, a reference numeral 11 is AV equipment, for example, which complies with IEEE 1394a-2000.

15 The AV equipment 11 is connected to a bridging device 13 through a network bus of a first network complying with the IEEE 1394 High Performance Serial Bus standard.

20 Also, the bridging device 13 can transmit/receive data to/from two or more pieces (two pieces in the drawing) of AV equipment 15 and 16 through a wireless network 14 of a second network, according to the IEEE 802. 11a standard and the like.

25 It is configured in this embodiment that the AV equipment 11 connected to the 1394 bus 12 specifies an arbitrary piece of AV equipment 15 or 16 connected to the wireless network 14 according to another

standard and executes transmission/reception of data to/from the arbitrary equipment.

FIG. 2 shows the details of the bridging device 13. The bridging device 13 comprises: a 1394
5 I/F (Interface) section 17; a wireless I/F section 18; a quantity detection section 19; an information collection section 20; a temporary-ID assignment section 21; an identification-information transmitting section 22; a bus reset section 23; an related-
10 identification-information storage section 24; and a transfer section 25.

The 1394 I/F section 17 is connected to the 1394 bus 12 and is an interface which executes transmission/reception of data to/from the AV equipment
15 11 in processing according to the IEEE 1394-1995 standard or the IEEE 1394a-2000 standard.

The wireless I/F section 18 is connected to the wireless network 14 and is an interface for executing transmission/reception of data to/from the AV equipment
20 15 or 16 in processing according to a standard for a wireless network.

The quantity detection section 19 detects through the wireless I/F section 18 the number of the pieces of AV equipment 15 and 16 which are connected to the
25 wireless network 14. The information collection section 20 collects through the wireless I/F section 18 various kinds of information on the pieces of AV

equipment 15 and 16 which are connected to the wireless network 14.

5 The temporary-ID assignment section 21 issues the corresponding number of temporary IDs (identifiers) to that of the pieces of AV equipment 15 and 16 detected in the quantity detection section 19 and assigns the temporary IDs to the pieces of AV equipment 15 and 16, respectively.

10 The identification-information transmitting section 22 is configured to transmit the IDs issued in the temporary-ID assignment section 21 to the 1394 bus 12 through the 1394 I/F section 17 in a state where the IDs are stored in Self_ID packets, respectively.

15 The bus reset section 23 is configured to reconstruct the 1394 bus 12 through the 1394 I/F section 17 in order to give information on the pieces of AV equipment 15 and 16 connected to the wireless network 14 to the AV equipment 11 on the 1394 bus 12, based on at least one of an output from the quantity
20 detection section 19 or that from the information collection section 20.

 The related-identification-information storage section 24 stores various information items about the AV equipments 15 and 16 connected to the wireless
25 network 14. The information items have been supplied from the information collection section 20. The section 24 stores the IDs of the AV equipments 15 and

16, which have been issued from the temporary-ID assignment section 21. In the storage section 24, the information items are stored in association with the IDs of the AV equipments 15 and 16.

5 The transfer section 25 converts the destination of a packet, among packets transmitted from the AV equipment 11 on the 1394 bus 12, with an ID, by which an arbitrary piece of AV equipment 15 or 16 on the wireless network 14 has been addressed, to that of the
10 AV equipment 15 or 16 on the wireless network 14 and reconstructs the packet to obtain a packet with a format according to a protocol meeting that of the wireless network 14.

 Hereinafter, operations will be explained in the
15 above configuration. In the first place, the AV equipment 11 and the bridging device 13 mutually recognize on the side of the 1394 bus 12 that only both of the pieces of equipment are connected to the network. Also, the bridging device 13, and the pieces
20 of AV equipment 15 and 16 mutually recognize on the side of the wireless network 14 that only three pieces of equipment are connected to the network 14.

 Under the above circumstances, the bridging device 13 identifies the pieces of AV equipment 15 and 16
25 connected to the wireless network 14. The quantity detection section 19 executes the above identification by detection, through the wireless I/F section 18, of

the number of the pieces of AV equipment 15 and 16 connected to the wireless network 14. Also, the information collection section 20 executes the above identification by collection, through the wireless I/F section 18, of various kinds of information on the pieces of AV equipment 15 and 16 connected to the wireless network 14.

The information which is collected in the information collection section 20 is as follows:

- 10 * IDs unique to the pieces of AV equipment 15 and 16, such as MAC (Media Access Control) addresses and EUI 64 identifiers.
- * Identification information on the protocols such as IP (Internet Protocol) addresses and Node_IDs according to the IEEE 1394 standard.
- 15 * Protocols, data types, and data formats which the pieces of AV equipment 15 and 16 can process, such as TCP (Transmission Control Protocol) and UDP (User Datagram Protocol), Subunit information for AV/C (audio video control), and formats of image data according to MPEG2-TS.
- 20 * Information which the pieces of AV equipment 15 and 16 store, such as names, names of manufacturers, versions, and icons for the pieces of equipment.
- 25 * Information on configurations of the pieces of AV equipment 15 and 16, such as data rates and buffer sizes with which information can be

transmitted/received.

Since it is shown that there has been a change in the configuration of the wireless network 14 when the number of the pieces of equipment detected in the quantity detection section 19 is one or more, or, when
5 the pieces of AV equipment 15 and 16 have been changed to different pieces of equipment from those of the collection result by the information collection section 20 even if the number of detection is not changed, the
10 configuration of the 1394 bus 12 is required to be changed.

In such a case, the bridging device 13 is configured to add the pieces of AV equipment 15 and 16 on the wireless network 14 to the 1394 bus 12. That
15 is, a number of IDs, equal to the number of pieces of equipment detected in the quantity detection section 19 (equivalent to Physical_IDs, for the IEEE 1394 standard is applied here as an example) are issued in the temporary-ID assignment section 21. Here, the
20 Physical_ID is called "a temporary ID", for the Physical_ID is changed at change in the configuration of the bus, that is, at reset of the bus in the IEEE 1394 standard.

When the bus reset section 23 detects, from at
25 least one of an output from the quantity detection section 19 and that from the information collection section 20, that the configuration of the wireless

network 14 is changed, the 1394 bus 12 is configured to be reconstructed (bus reset) according to the IEEE 1394 standard by the bus reset section 23 through the 1394 I/F section 17.

5 At the final stage of the bus reset, packets, called Self_ID packets, are generated in the 1394 I/F section 17 and are transmitted to the 1394 bus 12. There is, in a Self_ID packet, an area where a Physical_ID is stored, and a node (the AV equipment 11) 10 which receives the Self_ID packets detects how many nodes exist on the above 1394 bus 12. Thereby, after the Self_IDs are transmitted at the final stage of the bus reset, the 1394 I/F section 17 in the bridging device 13 sends the Self_IDs of the pieces of AV 15 equipment 15 and 16.

For example, when it is assumed that the AV equipment 11 sends a Self_ID packet of a Physical_ID (PHY_ID) = 0, the 1394 I/F section 17 sends Self_ID packets, respectively of a PHY_ID = 1 (for the AV 20 equipment 15), a PHY_ID = 2 (for the AV equipment 16), and a PHY_ID = 3 (for the equipment 17 itself, that is, the bridging device 13).

Then, the AV equipment 11 having received these Self_ID packets recognizes that four pieces, including 25 the equipment 11 itself, of equipment 11, 13, 15, and 16 are connected to the 1394 bus 12, (including virtual 1394 buses 26 and 27) as shown in FIG. 3.

Also, since the set membership among pieces of equipment in a network is defined immediately after starting of bus reset in the IEEE 1394 standard, a configuration in which PHY_IDs are assigned to the pieces of equipment on the wireless network 14 and a virtual set membership among the pieces of equipment is defined may be applied in the temporary-ID assignment section 21.

The set membership is transmitted to the AV equipment 11 on the 1394 bus 12 in a Self_ID packet. For example, it is defined as shown in FIG. 3 that the AV equipment 11 is a child of the bridging device 13; the AV equipment 16 is a child of the AV equipment 15; and the AV equipment 15 is a child of the bridging device 13 and a parent of the AV equipment 16.

In order to smoothly execute a series of operations for transmitting the above Self_ID packets, it is preferable that the bridging device 13 is a route node (the route node is a parent node and a node which is not a child node and which has the largest PHY_ID) on the 1394 bus 12. Thereby, there may be considered a configuration in which a route acquisition section (not shown) influences the 1394 I/F section 17 so that the bridging device 13 becomes a route node.

FIG. 4 shows a flow chart for a series of operations which transmit Self_ID packets. In the first place, processing is started (step S11) and the

bridging device 13 recognizes in step S12 that each of the 1394 bus 12 and the wireless network 14 individually forms a network.

Subsequently, the bridging device 13 detects in
5 step S13 the number of the pieces of AV equipment 15 and 16 which are connected to the wireless network 14 and judges in step S14 whether the number is one or more. Then, when it is decided that the number is not one or more (NO), the bridging device 13 ends the
10 processing (step S22).

Also, when it is decided in step S14 that the number is one or more (YES), the bridging device 13 collects in step S15 information on each of the AV
15 equipment 15 or 16 on the wireless network 14 and it is determined in step S16 whether there is a change in the information on the pieces of AV equipment 15 and 16.

Then, when it is decided that there is no change (NO), the processing of the bridging device 13 is returned to that of STEP S13. Also, when it is decided
20 in step S16 that there is a change (YES), the bridging device 13 makes, in step S17, a set relationship among the pieces of AV equipment 15 and 16 on the wireless network 14 for a case in which the pieces of equipment are virtually connected to the 1394 bus 12.

Subsequently, the bridging device 13 assigns, in
25 step S18, IDs to each piece of the AV equipment 15 and 16, considering the set membership for virtual

connection of the pieces of AV equipment 15 and 16.

In such a case, various kinds of information on the pieces of AV equipment 15 and 16 collected in step S15 and IDs, which have been issued in step S18
5 corresponding to each piece of the AV equipment 15 and 16, are stored in the related-identification-information storage section 24 in relation to each other.

Then, the bridging device 13 generates, in step
10 S19, Self_ID packets, by which the pieces of AV equipment 15 and 16 on the wireless network 14 are added to the 1394 bus 12, from the set membership for the virtual connection and the assigned IDs.

Thereafter, the bridge device 13 reconstructs the
15 1394 bus 12 (thus, performing bus reset) in step S20. In Step S21, the self_ID packets are transmitted to the 1394 bus 12. In step S22, the process is terminated.

Next, operations for a case in which data is transmitted from the AV equipment 11 to the AV
20 equipment 15 in a state where the AV equipment 11 recognizes that four pieces of equipment 11, 13, 15, and 16, including the equipment 11 itself, are connected to the 1394 bus 12 will be explained as one example.

25 That is, various kinds of information, collected in the information collection section 20, regarding the pieces of AV equipment 15 and 16 on the wireless

network 14, and IDs (PHY_IDs) assigned to the pieces of the AV equipment 15 and 16, have been stored in the above-described related-identification-information storage section 24 in relation to each other.

5 Usually, the AV equipment 11 inquires of each node on the 1394 bus 12 for the performance and the equipment type after the bus reset. But a configuration in which the bridging device 13 answers the inquiry as a proxy may also be applied. In this
10 case, information in the related-identification-information storage section 24 corresponding to the PHY_ID of the AV equipment under inquiry is supplied as an answer.

 Moreover, there may be considered an operation in
15 which each piece of the AV equipment 15 or 16 on the wireless network 14 is sequentially inquired through the transfer section 25 in the bridging device 13 in an actual manner whenever the above inquiry is made. The contents included in the inquiries may be reserved
20 in the related-identification-information storage section 24.

 For example, when a certain command is issued from the AV equipment 11 to the AV equipment 15, the AV equipment 11 uses the PHY_ID = 1, which has been
25 virtually assigned to the AV equipment 15, as a destination in order to transmit a packet as well as the case in which a command is transmitted to a piece

of equipment on the same bus. The transmitted packet is received in the 1394 I/F section 17 and transmitted to the transfer section 25.

5 In the transfer section 25, it is determined whether the destination is the PHY_ID assigned in the temporary-ID assignment section 21 and the destination is converted to a destination on the wireless network 14, referring to information in the related-identification-information storage section 24. Also,
10 if required, the packet is reconstructed to obtain a packet with a configuration suitable for the wireless network 14.

Then, the packet converted in the transfer section 25 is transmitted to the equipment 15 on the wireless
15 network 14 through the wireless I/F section 18, that is, data transmission from the AV equipment 11 to the AV equipment 15 is executed.

When an answering packet (acknowledgement) is transmitted back from the AV equipment 15, the
20 acknowledgement received through the wireless I/F section 18 is reconstructed in the transfer section 25 and is transmitted to the AV equipment 11 on the 1394 bus 12 through the 1394 I/F section 17. A configuration provided with means by which, when the
25 AV equipment 15 does not return the acknowledgement, the 1394 I/F section 17 in the bridging device 13 acts as means for returning the acknowledgement, may be

applied.

FIG. 5 shows a flow chart of operations for data transmission from the AV equipment 11 to the AV equipment 15. In the first place, processing is started (step S23) and, in step S24, the AV equipment 11 as the transmitting side sends to the 1394 bus 12 a Self_ID packet in which an ID (PHY_ID) having an address for the AV equipment 15 of the receiving side as a destination is stored.

Subsequently, the bridging device 13 receives the packet transmitted to the 1394 bus 12 in step S25 and it is determined at In STEP S26 whether the received packet is addressed to the AV equipment 15 or 16. When it is decided that the packet is not addressed to the AV equipment 15 or 16 on the network 14 (NO), the processing of the bridging device 13 is returned to that of STEP S25.

Also, when it is decided at the above-described STEP S26 that the received packet is addressed to the AV equipment 15 or 16 on the wireless network 14 (YES), the bridging device 13 specifies, in step S27, the AV equipment 15 on the wireless network 14 to which equipment the packet is required to be transferred, collating information, which has been reserved in the related-identification-information storage section 24, relating to the AV equipment 15 and 16 on the wireless network 14, with the ID of the received packet.

Subsequently, the bridging device 13 converts, in step S28, the format of the received packet to that complying with the protocol applied in the wireless network 14; the destination is converted in step S29 to that of the specified AV equipment 15 on the wireless network 14; and, in step S30, the packet is transmitted to the AV equipment 15, based on the protocol applied on the wireless network 14 to end the processing (step S31).

According to the above-described embodiments, it is possible, by transmitting the equal number of Self_ID packets to that of the pieces of AV equipment virtually connected to the AV equipment 11 on the 1394 bus 12, to easily identify pieces of equipment among networks to which different standards are applied, and to execute transmission/reception of a packet among the networks.

Also, since the pieces of equipment are virtually configured to be in a network on the same bus, communication can be realized according to a protocol even when the protocol cannot meet conditions for communication among different buses or even in an environment in which networks with different standards actually exist.

A case in which the pieces of AV equipment 15 and 16 on the wireless network 14 are virtually connected to the 1394 bus 12 has been explained in the

above-described embodiments. Conversely, the AV equipment 11 on the 1394 bus 12 may be configured to be connected to the wireless network 14 in a virtual manner.